

ERGOMAT®




Exceptional anti-fatigue matting

SELECTION GUIDE


ERGOMAT® STANDARD

In most dry environments, including cleanroom and static control areas, ERGOMAT STANDARD is the preferred choice. In combined rolling and standing environments, choose the SMOOTH ERGOMAT ANTISTAT. For other special applications, please consult the chart below to determine the most appropriate ERGOMAT for your working conditions. Refer to individual product sheets for further information.

	Dry usage area	Wet usage area	Static control	Cleanroom	Fire Retardant	Alkaline pH >9.5	Acidic pH <2.0	Welding area	Hot metal chips	Slip prevention	Autoclavable
ERGOMAT STANDARD	Recommended	Not Recommended	Recommended	Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended
ERGOMAT F-MAT	Recommended	Recommended	Not Recommended	Not Recommended	Recommended	Recommended	Recommended	Not Recommended	Not Recommended	Recommended	Not Recommended
ERGOMAT 100	Recommended	Recommended	Not Recommended	Not Recommended	Not Recommended	Recommended	Recommended	Not Recommended	Not Recommended	Recommended	Not Recommended
SMOOTH ERGOMAT ANTISTAT	Recommended	Not Recommended	Recommended	Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended
ERGOMAT SOFTLINE	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Recommended	Recommended	Not Recommended	Not Recommended
ERGOMAT NITRIL	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Recommended	Recommended	Not Recommended	Not Recommended
ERGOMAT NITRIL ESD	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Recommended	Recommended	Recommended	Not Recommended	Not Recommended

 Solid Color = Recommended
 Light Tone = Acceptable
 No Color = Not Recommended

ERGOMAT STANDARD
8 year warranty




ERGOMAT F-MAT
3 year warranty



ERGOMAT 100
3 year warranty



SMOOTH ERGOMAT ANTISTAT
3 year warranty



ERGOMAT SOFTLINE
3 year warranty



ERGOMAT NITRIL
3 year warranty



ERGOMAT NITRIL ESD
3 year warranty



Chemical Resistance Chart

TOLERANCES	ERGOMAT STANDARD	ERGOMAT F-MAT	ERGOMAT 100	SMOOTH ERGOMAT ANTISTAT	ERGOMAT SOFTLINE	ERGOMAT NITRIL	ERGOMAT NITRIL ESD
The Weather	Light Tone	Medium Tone	Medium Tone	Light Tone	Solid Color	Solid Color	Solid Color
Mineral Oils	Medium Tone	Medium Tone	Medium Tone	Light Tone	Solid Color	Solid Color	Solid Color
Vegetable Oils	Medium Tone	Medium Tone	Medium Tone	Light Tone	Solid Color	Solid Color	Solid Color
Cutting compound	Light Tone	Medium Tone	Medium Tone	Light Tone	Solid Color	Solid Color	Solid Color
Cutting compound including compounds of esters	No Color	Light Tone	Light Tone	No Color	No Color	No Color	No Color
Alkaline detergents & alkalines 7 < pH < 9.5	Medium Tone	Medium Tone	Medium Tone	Light Tone	Solid Color	Solid Color	Solid Color
Alkaline detergents & alkalines pH > 9.5	Light Tone	Light Tone	Light Tone	Light Tone	Light Tone	Light Tone	Light Tone
Acids 7 > pH > 2	Light Tone	Medium Tone	Medium Tone	Light Tone	Solid Color	Solid Color	Solid Color
Acids pH < 2	No Color	Light Tone	Light Tone	No Color	No Color	No Color	No Color
Vinegar	Light Tone	Medium Tone	Medium Tone	Light Tone	Solid Color	Solid Color	Solid Color
Disinfectants	Light Tone	Medium Tone	Medium Tone	Light Tone	Solid Color	Solid Color	Solid Color
Chloride solutions (0.2% active chlorine)	Light Tone	Light Tone	Light Tone	Light Tone	Light Tone	Light Tone	Light Tone

Key:

	Solid Color = Highly Recommended
	Medium Tone = Recommended
	Light Tone = Acceptable
	No Color = Not Recommended

Shannahan
Ergonomics &
Technology
314-965-2800

ERGOMAT anti-fatigue matting is not recommended for use in the following chemical environments:

Benzene based solvents (aromatic carbon hydrides); Halogenated carbon hydrides; Phthalates (and related softeners); Acetates and ester compounds; Compounds including amines; Ketones (acetone).

Please Note:

This chart is based on severe and extended submersion in the chemical tested. Results may vary with less severe, short term exposure – such as from splashes and vapors. The manufacturer will supply samples as needed for testing under specific chemical conditions.

Please contact our customer service department at 800.357.2111 with any questions you may have.

Shannahan
Ergonomics &
Technology
314-965-2800

ERGOMAT® is a division of:

Tinby LLC
871 Canterbury Road
Westlake, Ohio 44145

Sales: 800.357.2111
Phone: 440.899.1700
Fax: 440.899.1702

E-Mail: info@ergomat.com
Web Site: www.ergomat.com